Product Data Sheet SORB®MS Marine Solutions Oil-Barrier „PERMANENT“

Product Information:

Application

- suitable for longtime usage near-shore, harbors and in-land containment operations

Key Features

- built to outlast heavy debris concentrations and current speeds
- Heavy-duty, solid floats are intended for long-term applications with minimal and basic maintenance
- flexible and highly resistant to abrasion
- designed for long-term, permanent installations
- strategically positioned lifting handles and anchoring points along the boom

Technical Data

Manufactured from high durability belt material. Rotary moulded polyethylene (HDPE) floats filled with polystyrene foam provide unmatched reliability and minimum maintenance. Steel blocks provide excellent weight distribution. Sections are connected with ASTM-Z end connectors as well other types upon clients request.

Storage

- Hydraulic Reel
- Storage Rack
- Container
- Trailer

Product Data Sheet
SORB®MS Marine Solutions
Oil-Barrier „PERMANENT“

Technical Data

Article no. 100579	**-450P**	**-600P**	**-920P**
Height	450 mm	600 mm	920 mm
Freeboard	100 mm	250 mm	320 mm
Draft	350 mm	350 mm	600 mm
Length	10 m		
Fabric	EP 125 Belt double ply 7,1 kg/m²		
Belt Thickness	6 mm		
Belt Breaking Strength	250 N/mm (DIN 22102)		
Boyancy / Weight Ratio	3,5/1	3,0/1	2,5/1
Connectors	ASTM Z-Type		
Weight	11 kg/m	12,1 kg/m	14,5 kg/m
Floats	Rotary Moulded HDPE, EPS filled		
Floats Dimensions	450 x 250 x140 mm		
Ballast	galvanized steel blocks		
Operational Temperature	-10° bis 60° C (Wasser)		
Colour	Black with yellow floats		

Department of Allegro
Capital, Logistics, Services & More GmbH

Allegro Capital, Logistics, Services & More GmbH
Klosterhofweg 64
41199 Mönchengladbach

phone: +49 2166 1268-160
e-mail: service@sorb-xt.de
www.sorb-xt.de

managing director: Wolf-Peter Korth
tax number: 102/5801/1903
VAT number.: DE308746153
CRN: 19194

bank details:
Commerzbank AG Mönchengladbach
IBAN: DE82 3104 0015 0162 1028 00
BIC: COBADEFFXXX